


Superior Series

SUP310-330

10~30kVA, 3:3 phase, PF 0.9



LCD Touch Screen

The Superior Series Double Conversion true online Series, featured with DSP-controlled technology, superior input Voltage window for energy ECO mode, parallel capability (for 10KVA, 30KVA 3/3), smart fan speed control, optional powerful charger, is an ideal solution to your computer center, network center, communication system, automatic control system or other critical system.

Features

- Online-Double conversion.
- Output transfer time is 0ms
- Full digital control (DSP)
- Input current harmonic: 3%
- Charging/Rectifier/Inverter fully digital control technology
- Wide input voltage range: 208~478Vac
- Wide input frequency range: 40~70Hz
- ECO function.
- PFC technology
- Output power factor: 0.9
- Intelligent charging management
- Optimization battery group, QTY: 10 ~ 30KVA (16/18/20 pcs optional).
- LCD/LED double display Touch Screen Optional.
- Communication port: USB/RS232/RS485
- DC start
- Options: SNMP card/Relay card
- EPO function
- Common battery group
- The output can meet 100% unbalanced load.
- Parallel port/dry contact Optional



Technical Specifications:

MODEL	310	315	320	330	340
Capacity	10KVA/9KW	15KVA/13.5KW	20KVA/18KW	30KVA/27KW	40KVA/36KW
INPUT					
Nominal Voltage	380/400/415Vac, 3Ph+N+PE				
Operating Voltage Range	208-478Vac				
Operating Frequency Range	50Hz: 45-55Hz / 60Hz: 54-66Hz				
Power Factor	>0.99				
THDi	<3% (100% linear load)				
Bypass voltage range	380Vac Max. voltage: +25% (optimal +10%, +15%, +20%) 400Vac Max. voltage: +20% (optimal +10%, +15%), 415Vac Max. voltage: +15% (optimal +10%), Min. volyage: -45% (optimal -20%, -30%) Frequency synchronize tracing range: $\pm 10\%$				
OUTPUT					
Output voltage	380/400/415Vac, 3Ph+N+PE				
Voltage regulation.	$\pm 1\%$				
Power Factor	0.9 (Optional 1.0)				
Output frequency	1- Line Mode: $\pm 1\%$ / +2% / +4% / +5% / +10% of the rated frequency (option) 2- Battery Mode: (50/60 ± 0.1) Hz				
Crest factor	3 : 1				
THDv	<1% with linear load <5% with non linear load				
Efficiency	93.5%	94.5%			
BATTERY					
Battery voltage	Standard 20Pcs x 12V Battery Quantity: 16/18/20Pcs				
Charge Current (A)	4.5A				
System Features					
Transfer time	Utility to Battery: 0ms, Utility to bypass: 0ms				
Over load	Load<110%: 60Min; <125%: 10Min; >150% tuen to bypass mode				
Alarm	over load, utility abnormalm UPS fault, battery low, high and low Voltage				
Protection	short crcuitm overload, over temperature, battery lowm fan fault. Alarm				
Remot LCD	Support				
Communication	USB, RS485, Parralel port, Coupler dry. Contact, Intelligent slot, SNMP, card (option), relay. Card (option)				
ENVIRONMENTAL					
Operating Temperature	0-40 C				
Storage temperature	-25-55 C (No battery)				
Humidity	0-95% (non condensing)				
Altitude	<1500m. When>1500m				
Noise level	<55dB	<58dB			
PHYSICAL					
Dimension D x W x H (mm)	828x250x868				
Net weight (Kg)	115	170	171	223	244
STANDARDS					
Safety	IEC/EN62040-1, IEC/EN60950-1				
EMC	IEC/EN62040-2, IEC61000-4-2 IEC61000-4-3, IEC61000-4-4, IEC61000-4-8; IEC61000-4-6; IEC61000-4-5				

